

SJIII 4632

Skyjack 32ft Electric Scissor Lift



SPECIFICATIONS

SJIII 4632

A Work Height	11.75 m
B Raised Platform Height	9.75 m
C Lowered Platform Height	1.23 m
D Overall Width	1.17 m
E Overall Length	2.31 m
F Stowed Height (Rails Up)	2.24 m
G Stowed Height (Rails Down)	1.88 m
H Platform Width (Inside Dimension)	1.07 m
I Platform Length (Inside Dimension)	2.13 m
Extension Deck (Roll Out)	0.91 m
Ground Clearance (Stowed)	8.89 cm
Ground Clearance (raised)	1.91 cm
Wheelbase	1.75 m
Weight	2935 kg
Gradeability	25%
Turning Radius (Inside)	1.21 m
Turning Radius (Outside)	2.37 m
Lift Time (With Rated Load)	59 sec
Drive Speed (Stowed)	2.4 km/h
Drive Speed (Raised)	1.1 km/h
Maximum Drive Height	Full Height
Capacity (Overall)	318 kg
Maximum # of Persons (0 wind rating)	2
Maximum # of Persons (12.5 m/sec wind rating)	1

STANDARD FEATURES

- Drivable at full height
- Variable speed, rear two wheel hydraulic drive • Wet disc SAHR brakes
- Proportional controls for drive & lift functions
- 0.91 m roll out extension deck
- 24V DC power source
- Low voltage battery protection
- 25% gradeability
- Solid rubber, non-marking tyres
- Pothole protection system
- Wiring for AC outlet on platform
- Tilt alarm with drive & lift cut-out • All motion audible alarm
- Overload sensing system Lowering warning system
- Lanyard attachment points • Operator horn
- Half height spring hinged gate
- Hinged railing system
- Forklift pockets and tie down/lift lugs
- Analog control system
- Colour coded and numbered wiring system

OPTIONS

- Flashing light
- Dual flashing lights
- Shop airline to platform
- 250 Ah batteries
- Full height spring hinged gate

‡ Capacities, and machine weights may differ when options are added

