

## JCPT0607PA

## Dingli 19ft Scissor Lift with Trailer

Size	Metric	British
A. Max. Working Height	5.60m	18ft 5in
B. Max. Platform Height	3.60m	11ft 10in
C. Overall Length	1.44m	4ft 9in
D. Overall Width	0.76m	2ft 6in
E. Overall Height(Rails Up)	1.99m	6ft 6in
F. Overall Height(Rails Down)	1.62m	5ft 4in
Platform Size(Length>Width)	1.29mx0.70m	4ft 3inx 2ft 4i
Platform Extension Size G	0.60m	2ft
Ground Clearance (Stowed/Raised)	0.06m/0.015m	2in/1in
Wheelbase H	1.05m	3ft 5in
Turning Radius(Inside/Outside)	0.40m/1.55m	1ft 4in/5ft 1in
Tyres	230x80mm	230×80mm

Performance		
S.W.L	240kg	529lb
S.W.L On Extension	100kg	220lb
Max. Occupants (Indoor/Outdoor)	2/1	2/1
Gradeability	25%	25%
Travel Speed(Stowed)	4.0km/h	2.49mph
Travel Speed(Raised)	0.6km/h	0.37mph
Max. Working Slope	X-1.5°/Y-3°	X-1.5°/Y-3°
Up/Down Speed	22/22sec	22/22sec

Weight		
Overall Weight	920kg	2028lb

Power			
Battery	24V/85Ah	24V/85Ah	
Charger	24V/15A	24V/15A	
Driving Motor	2x24VDC/0.7kW	2x24VDC/0.7kW	
Lifting Motor	24VDC/1.4kW	24VDC/1.4kW	





## **STANDARD FEATURES**

- · Standard Items
- · Proportional Joystick Controls
- Self-Locking Gates
- One-Way Platform Extension Deck
- Drivable At Full Height
- · Non-Marking Tyres
- Two-Wheel Drive
- · Two-Wheel Steering
- Automatic Braking System
- · Emergency Descent System
- Onboard Fault Diagnostic System
- Tilt Alarm
- · Motion Alarm
- Horn
- Hour Meter
- Safety Arm For Troubleshooting
- Standard Transport Forklift Holes
- · Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- · Automatic Pothole Protection
- Drive Enable
- Charging Indicator
- Manual Brake Release
- · Lanyard Attachment Point
- Tie-Down And Lifting Points
- Platform Load Sense System
- · Emergency Stop Button