

Fuso Canter

Canter Light Duty (6-Wheeler)



Dimensions & Weight		FE73	FE84	FE85-S	FE85-L	FG83 4x4
Overall Length / Width / Height	(mm)	5,785 / 1,875 / 2,110	6,685 / 2,035 / 2,215	7,185 / 2,145 / 2,220	7,735 / 2,145 / 2,220	5,935 / 2,035 / 2,505
Wheelbase	(mm)	3,400	3,850	4,300	4,750	3,415
Wheel Tread (Front / Rear)	(mm)	1,390 / 1,435	1,665 / 1,560	1,665 / 1,670	1,665 / 1,670	1,665 / 1,560
Cab to Rear Axle (C.A.)	(mm)	2,824	3,275	3,790	4,305	2,905
Cab to End Frame (C.E.)	(mm)	4,219	4,970	5,535	6,150	4,300
Min. Ground Clearance	(mm)	200	200	210	210	210
Curb Weight	(kg)	2,085	2,370	2,425	2,460	2,585
Payload	(kg)	2,405	4,130	6,125	6,090	2,915
Gross Vehicle Weight (GVW)	(kg)	4,490	6,500	8,550	8,550	5,500
ENGINE						
Model		4P10 -KAT2	4P10 -KAT2	4P10 -KAT2	4P10 -KAT2	4P10 -KAT2
Type			Turbo-Intercooler, DOHC, Common-Rail Direct Injection, Diesel Engine			
Cylinders		4 In-Line	4 In-Line	4 In-Line	4 In-Line	4 In-Lie
Displacement	(cc)	2,998	2,998	2,998	2,998	2,998
Max. Power	(Ps/rpm)	131 / 3,500	150 / 3,500	150 / 3,500	150 / 3,500	150 / 3,500
Max. Torque	(N-m/rpm)	300 / 1,300	370 / 1,320	370 / 1,320	370 / 1,320	370 / 1,320
Fuel Tank Capacity	(L)	100	100	100	100	100
TRANSMISSION						
Drive System		4x2	4x2	4x2	4x2	4x4
Type			5 Forward, 1 Reverse M/T (Synchronesh Type)			
Final Gear Ratio		5.285	5.714	6.166	6.166	5.285
AXLE						
Front/Rear		Reverse Elliot "I" Beam / Fully Floating				
SUSPENSION						
Front		Laminated Leaf Springs with Shock Absorbers Laminated Leaf Springs with Shock Absorbers Hydraulic Double Acting Telescopic				
Rear						
Shock Absorber (Front and Rear)						
BRAKE						
Service		Disk Brake – Dual Circuit				Drum Brake – Dual Circuit